

CERTIFICATE

of Conformity of the Factory Production Control

1922 - CPR - 1498

In compliance with Regulation (EU) No 305/2011 of the European Parliament and of the council of 9 March 2011 (the Construction Products Regulation or CPR), this certificate applies to the construction products

Chimneys. Requirements for metal chimneys. System chimney products. Single and double wall metal system chimney elements

(The relevant thicknesses and diameters of the product are described in Annex I, that is an inseparable part of this certificate.)

placed on the market under the name or trade mark of

LLC «Vent Ustriy»

92a, Dekabrystiv Street, Vasylkiv City, Kyiv region 08606, Ukraine

and produced in the manufacturing plant

LLC «Vent Ustriy»

60, Poleva street, Vasylkiv City, Kyiv region 08606, Ukraine

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in Annex ZA of the standard

EN 1856-1:2009


under system 2+ are applied and that the factory production control is assessed to be in conformity with the applicable requirements.

This certificate was first issued on 16.02.2021 and will remain valid until 16.02.2027 as long as neither the harmonised standard, the construction product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly, unless suspended or withdrawn by the notified factory production control certification body. The certificate is supported through annual surveillance audit and is reissued after each surveillance audit. The validity of the certificate may be confirmed in the CE register at the web address www.dedal-bg.net.



Manager:

Banuba



dipl. eng. Anna Vasileva

Issued:
Burgas, 13 March 2026

Ref. No. 05-00

ANNEX I TO CERTIFICATE OF CONFORMITY OF THE FACTORY PRODUCTION CONTROL 1922-CPR-1498/13.03.2026

**Chimneys. Requirements for metal chimneys. System chimney products.
Single and double wall metal system chimney elements acc. to EN 1856-1:2009**

Description	Designation
<p>Single wall metal chimneys, material: stainless steel, No. 1.4301, thicknesses: 0,5 mm, 0,8 mm and 1,00 mm</p> <p>Diameters: 80 mm, 100 mm, 110 mm, 120 mm, 130 mm, 140 mm, 150 mm, 160 mm, 180 mm, 200 mm, 220 mm, 250 mm;</p>	<p>EN 1856-1- T600-N1-D-Vm-L20050-G (100)</p> <p>EN 1856-1- T600-N1-W-Vm-L20050-G (100)</p> <p>EN 1856-1- T600-N1-D-Vm-L20080-G (100)</p> <p>EN 1856-1- T600-N1-W-Vm-L20080-G (100)</p> <p>EN 1856-1- T600-N1-D-Vm-L20100-G (100)</p> <p>EN 1856-1- T600-N1-W-Vm-L20100-G (100)</p>
<p>Double wall metal chimneys, material: stainless steel, No. 1.4301, thickness 0,5 mm, 0,8 mm and 1,00 mm</p> <p>Diameters (internal and external): 80/ 140 mm, 100/ 160 mm, 110/180 mm, 120/ 180 mm, 130/ 200 mm, 140/ 200 mm, 150/ 220 mm, 160/220 mm, 180/ 250 mm, 200/ 260 mm, 220/ 280 mm, 250/ 320 mm.</p> <p>Insulation: Mineral wool, density 60 kg/m³</p>	<p>EN 1856-1- T450-N1-D-Vm-L20050-G (30)</p> <p>EN 1856-1-T450-N1-W-Vm-L20050-G (30)</p> <p>EN 1856-1- T450-N1-D-Vm-L20080-G (30)</p> <p>EN 1856-1-T450-N1-W-Vm-L20080-G (30)</p> <p>EN 1856-1- T450-N1-D-Vm-L20100-G (30)</p> <p>EN 1856-1-T450-N1-W-Vm-L20100-G (30)</p>

